

DMD 331 选型表

DMD 331		[] - [] - [] - [] - [] - [] - [] - [] - [] - []																		
测量压力	差压	7	3	0																
额定量程	[bar]																			
	0.2				F															
	0.4				A															
	1.0				B															
	2.5				C															
	6.0				D															
	16				E															
	用户需求				9															请咨询
差压量程	[bar]	F	A	B	C	D	E													
	0.02	■						0	2	0	0									
	0.04	■	■					0	4	0	0									
	0.10	■	■	■				1	0	0	0									
	0.25	■	■	■	■			2	5	0	0									
	0.40	■	■	■	■	■		4	0	0	0									
	0.60	■	■	■	■	■	■	6	0	0	0									
	1.0	■	■	■	■	■	■	1	0	0	1									
	2.5	■	■	■	■	■	■	2	5	0	1									
	4.0	■	■	■	■	■	■	4	0	0	1									
	6.0	■	■	■	■	■	■	6	0	0	1									
	10	■	■	■	■	■	■	1	0	0	2									
	16	■	■	■	■	■	■	1	6	0	2									
	用户需求							9	9	9	9									请咨询
输出	4 ... 20 mA / 2线制											1								
	0 ... 10 V / 3线制											3								
	用户需求											9								请咨询
精度 (根据 BFSL)	0.25%											5								
	用户需求											9								请咨询
电气连接	ISO 4400 插头与插座											1	0	0						
	Brad Harrison® - Mini Change											B	0	0						请咨询
	用户需求											9	9	9						请咨询
压力接口及过程连接件	G1/2" EN 837												2	0	0					
	7/16" UNF DIN 3866												U	0	0					
	G1/4" 内螺纹												J	0	0					
	用户需求												9	9	9					请咨询
密封件	FKM															1				
	用户需求															9				请咨询
特殊型号	标准																	0	0	0
	用户需求																	9	9	9
																				请咨询

本数据资料仅用于描述该产品技术参数，并不保证其技术性能。所作任何修改恕不另行通知。

