

DMP 343 选型表

DMP 343

□	□	□	-	□	□	□	□	-	□	□	-	□	□	□	-	□	□	□
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

测量压力		表压	1	0	0													
额定量程		[mbar]																
		10	0	1	0	0												
		20	0	2	0	0												
		40	0	4	0	0												
		60	0	6	0	0												
		100	1	0	0	0												
		160	1	6	0	0												
		250	2	5	0	0												
		400	4	0	0	0												
		600	6	0	0	0												
		1000	1	0	0	1												
		-1000 ... 0	X	1	0	2												
		用户需求	9	9	9	9												请咨询
输出																		
		4 ... 20 mA / 2线制								1								
		0 ... 20 mA / 3线制								2								
		0 ... 10 V / 3线制								3								
		防爆 Ex 4 ... 20 mA / 2线制								E								
		用户需求								9								请咨询
精度 (根据 BFSL)																		
		标准 P _N > 100 mbar	0.175%							3								
		标准 P _N ≤ 100 mbar	0.25%							5								
电气连接																		
		ISO 4400 插头与插座								1	0	0						
		Binder Serie 723 (5针)								2	0	0						
		电缆压盖及线缆 ^{1,2}								4	0	0						
		线缆出口 ¹								T	R	0						
		Buccaneer 插头 IP68 ³								5	0	0						
		M12x1 (4针)								M	0	0						
		不锈钢防护壳								8	0	0						
		用户需求								9	9	9						请咨询
压力接口及过程连接件																		
		G1/2" DIN 3852								1	0	0						
		G1/2" EN 837								2	0	0						
		G1/4" DIN 3852								3	0	0						
		G1/4" EN 837								4	0	0						
		用户需求								9	9	9						请咨询
特殊型号																		
		标准											0	0	0			
		用户需求											9	9	9			请咨询

¹ 可选各种线缆和长度

² 标准: 2 m PVC 线缆 (无大气管), 可选配有大气管线缆

³ 要求使用配有大气管线缆

