

Ordering code LMK 331

LMK 331

- - - - - - -

Pressure										
gauge in bar		4	6	0						
gauge in mH ₂ O		4	6	1						
Input	[mH₂O]	[bar]								
	4.0	0.40	4	0	0	0				
	6.0	0.60	6	0	0	0				
	10	1.0	1	0	0	1				
	16	1.6	1	6	0	1				
	25	2.5	2	5	0	1				
	40	4.0	4	0	0	1				
	60	6.0	6	0	0	1				
	100	10	1	0	0	2				
	160	16	1	6	0	2				
	250	25	2	5	0	2				
	400	40	4	0	0	2				
	600	60	6	0	0	2				
	customer		9	9	9	9				consult
Analogue output										
	4 ... 20 mA / 2-wire						1			
	0 ... 20 mA / 3-wire						2			
	0 ... 10 V / 3-wire						3			
	Intrinsic safety 4 ... 20 mA / 2-wire						E			
	SIL2 4 ... 20 mA / 2-wire						1S			
	SIL2 with Intrinsic safety									
	4 ... 20 mA / 2-wire						ES			
	customer						9			consult
Accuracy										
	0.5 %						5			
	customer						9			consult
Electrical connection										
	Male and female plug ISO 4400						1	0	0	
	Male plug Binder series 723 (5-pin)						2	0	0	
	Cable outlet with PVC cable						T	A	0	
	Cable outlet with cable						T	R	0	
	Male plug M12x1 (4-pin) / metal						M	1	0	
	compact field housing									
	stainless steel 1.4305						8	5	0	
	customer						9	9	9	consult
Mechanical connection										
	G3/4" DIN 3852 with flush sensor						K	0	0	
	customer						9	9	9	consult
Seals										
	FKM								1	
	NBR								5	
	EPDM								3	
	customer								9	consult
Pressure port										
	Stainless steel 1.4404 (316L)								1	
	for P _N ≤ 25 bar								B	
	customer								9	consult
Diaphragm										
	Ceramics Al ₂ O ₃ 96%								2	
	customer								9	consult
Special version										
	standard								0	0
	customer								9	9
										consult

¹ only possible for pressure port of stainless steel
² Ex-protection not possible with plastic pressure port
³ standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 ... 70 °C)

This price list contains product specification; properties are not guaranteed. Detailed information about options are defined in the datasheet. Subject to change without notice.

