

Ordering code LMK 351

**LMK 351**

□□□ - □□□□ - □ - □ - □□□ - □□□□ - □ - □ - □ - □□□

<b>Pressure</b>									
	in bar	4	7	0					
	in mH <sub>2</sub> O	4	7	1					
<b>Input</b>									
	[mH <sub>2</sub> O]	[bar]							
	0.4	0.04	0	4	0	0			
	0.6	0.06	0	6	0	0			
	1.0	0.10	1	0	0	0			
	1.6	0.16	1	6	0	0			
	2.5	0.25	2	5	0	0			
	4.0	0.40	4	0	0	0			
	6.0	0.60	6	0	0	0			
	10	1.0	1	0	0	1			
	16	1.6	1	6	0	1			
	25	2.5	2	5	0	1			
	40	4.0	4	0	0	1			
	60	6.0	6	0	0	1			
	100	10	1	0	0	2			
	200	20	2	0	0	2			
	customer		9	9	9	9			consult
<b>Output</b>									
	4 ... 20 mA / 2-wire					1			
	0 ... 10 V / 3-wire					3			
	Intrinsic safety 4 ... 20 mA / 2-wire					E			
	customer					9			consult
<b>Accuracy</b>									
	standard	0.35 %				3			
	option	0.25 %				2			
	customer					9			consult
<b>Electrical connection</b>									
	Male and female plug ISO 4400					1	0	0	
	Male plug Binder series 723 (5-pin)					2	0	0	
	Cable outlet with PVC-cable <sup>1</sup>					T	A	0	
	Cable outlet <sup>2</sup>					T	R	0	
	Male plug M12x1 (4-pin) / metal					M	1	0	
	compact field housing					8	5	0	
	customer					9	9	9	consult
<b>Mechanical connection</b>									
	G1 1/2" DIN 3852 with flush sensor					M	0	0	
	customer					9	9	9	consult
<b>Seals</b>									
	FKM							1	
	EPDM							3	
	FFKM							7	
	customer							9	consult
<b>Pressure port</b>									
	Stainless steel 1.4404 (316L)							1	
	PVDF <sup>3</sup>							B	
	customer							9	consult
<b>Diaphragm</b>									
	Ceramics Al <sub>2</sub> O <sub>3</sub> 96%							2	
	Ceramics Al <sub>2</sub> O <sub>3</sub> 99.9%							C	
	customer							9	consult
<b>Special version</b>									
	standard							0	0
	customer							9	9
									consult

<sup>1</sup> standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 ... 70 °C)  
<sup>2</sup> cable with ventilation tube (code TR0 = PVC cable), different cable types and lengths available, price without cable  
<sup>3</sup> not possible in combination with compact field housing

