Fax: +49 (0) 92 35 / 98 11 -11

BD SENSORS® pressure measurement

Ordering code XMD

XMD ☐☐☐-☐☐☐☐-☐☐-☐-☐-☐☐☐-☐☐☐-1-☐-1-☐☐☐

Pressure																																
differential pressure	3	4	0																													
Input [mbar]																																
0 ... 75				0	7	5	0																									
0 ... 400				4	0	0	0																									
0 ... 2000				2	0	0	1																									
customer				9	9	9	9																									consult
Design																																
with display								A	0																							
without display								A	N																							
Output																																
Intrinsic safety ia 4 ... 20 mA / 2-wire (intrinsically safe version) with HART®-communication										I																						
Intrinsic safety d 4 ... 20 mA / 2-wire [1] (explosion proof housing) with HART®-communication										G																						in preparation
customer										9																						consult
Accuracy																																
0.1 %												1																				
Electrical connection																																
terminal clamp														A	K	0																
customer														9	9	9																consult
Mechanical connection																																
internal thread 1/4" - 18 NPT																		N	5	6												
Seals																																
FKM																							1									
EPDM																							3									
Special version																																
standard																											0	0	0			
customer																											9	9	9			consult

[1] HART® is a registered trade mark of HART Communication Foundation

This price list contains product specification; properties are not guaranteed. Detailed information about options are defined in the datasheet. Subject to change without notice.

BD SENSORS GmbH
BD-Sensors-Straße 1
D - 95199 Thierstein
Telefon +49 (0) 92 35 / 98 11- 0
Telefax +49 (0) 92 35 / 98 11- 11
www.bdsensors.com
info@bdsensors.de