

## 18.605 G 选型表

**18.605 G** -     -   -   -   -     -     -

额定量程		[mH <sub>2</sub> O]	[bar]																
	1.0	0.1	<sup>1</sup>	1	0	0	0												
	2.5	0.25		2	5	0	0												
	4.0	0.4		4	0	0	0												
	6.0	0.6		6	0	0	0												
	10	1.0		1	0	0	1												
		用户需求		9	9	9	9												请咨询
测量压力																			
	压力 bar							B											
	液位 mH <sub>2</sub> O							M											
	用户需求							9											请咨询
输出																			
	4 ... 20 mA / 2 线制																		1
	0 ... 10 V / 3 线制																		3
	0.5 ... 4.5 V / 3 线制, 比例输出																		R
	用户需求																		9
																			请咨询
精度 (根据BFSL)																			
	0.25%																		5
	用户需求																		9
																			请咨询
电气连接																			
	PVC 线缆																		1
	用户需求																		9
																			请咨询
线缆长度																			
	3 m																		0 0 3
	6 m																		0 0 6
	9 m																		0 0 9
	12 m																		0 1 2
	用户需求																		9 9 9
																			请咨询
压力接口及过程连接件																			
	G1/4" DIN 3852																		3 0 0
	用户需求																		9 9 9
																			请咨询
压力接口及过程连接 密封件																			
	FKM																		1
	用户需求																		9
																			请咨询
特殊型号																			
	标准																		0 0 0
	用户需求																		9 9 9
																			请咨询

<sup>1</sup> 压力量程 ≤ 160 mbar 时, 精度 ≤ ±0.5% FSO BFSL (≤ ±1% FSO IEC 60770)