

Ordering code DMK 351P

DMK 351P



Pressure																				
	gauge	2	9	5																
	absolute ¹	2	9	6																
Input		[mH ₂ O]	[bar]																	
		0.4	0.04	0	4	0	0													
		0.6	0.06	0	6	0	0													
		1.0	0.10	1	0	0	0													
		1.6	0.16	1	6	0	0													
		2.5	0.25	2	5	0	0													
		4.0	0.40	4	0	0	0													
		6.0	0.60	6	0	0	0													
		10	1.0	1	0	0	1													
		16	1.6	1	6	0	1													
		25	2.5	2	5	0	1													
		40	4.0	4	0	0	1													
		60	6.0	6	0	0	1													
		100	10	1	0	0	2													
		160	16	1	6	0	2													
		200	20	2	0	0	2													
	customer			9	9	9	9													consult
Output																				
	4 ... 20 mA / 2-wire							1												
	0 ... 10 V / 3-wire							3												consult
	Intrinsic safety 4 ... 20 mA / 2-wire							E												
	customer							9												consult
Accuracy																				
	standard	0.35 %						3												
	option	0.25 %						2												
	customer							9												consult
Electrical connection																				
	Male and female plug ISO 4400							1	0	0										
	Cable outlet with PVC cable ²							T	A	0										
	Binder series 723							2	0	0										
	Compact field housing							8	5	0										
	Cable outlet							T	R	0										
	Male plug M12x1 (4-pin) / metal							M	1	0										
	customer							9	9	9										consult
Mechanical connection																				
	G 1 1/2" DIN flush (DIN 3852)							M	0	0										
	Clamp DN 32 (DIN 32676)							C	6	2										
	Clamp DN 50 (DIN 32676)							C	6	3										
	Dairy pipe DN 40 (DIN 11851) ³							M	7	5										
	Dairy pipe DN 50 (DIN 11851) ³							M	7	6										
	Varivent® DN 40/50							P	4	1										consult
	Flange DN 25 / PN 40 (DIN 2501)							F	2	0										consult
	Flange DN 50 / PN 40 (DIN 2501)							F	2	3										consult
	Flange DN 80 / PN 16 (DIN 2501)							F	1	4										consult
	customer							9	9	9										consult
Seals																				
	FKM																			1
	EPDM																			3
	customer																			9
Pressure port																				
	Stainless steel 1.4404 (316L)																			1
	customer																			9
Diaphragm																				
	Ceramics Al ₂ O ₃ 96 %																			2
	Ceramics Al ₂ O ₃ 99.9 %																			C
	customer																			9
Special version																				
	standard																			0 0 0
	customer																			9 9 9

¹ absolute pressure from 0.04 bar up to 0.25 bar on request

² standard: 2 m PVC cable without ventilation tube

³ The cup nut has to be mounted by production of pressure transmitter with electrical connection field housing and mechanical connection dairy pipe.

The cup nut has to be ordered as separate position.

Varivent® is a brand name of GEA Tuchenhagen GmbH

